



technical specification pb-8002 protocole®

PHYSICAL DIMENSIONS

10 panels PB-8002

Standard Dimensions Outside: 171,4 cm x 194,5 cm x 173,5 cm

Acoustic Environment: Surpasses ISO-4043 International Standard (last version)

STANDARD	DIMENSION	WEIGHT
Standard panel (3)	85,7 cm x 194,5 cm	10,00 kg
Window panel (4)	85,7 cm x 194,5 cm	14,10 kg
Door panel (1)	85,7 cm x 194,5 cm	17,00 kg
Roof panel (2)	85,7 cm x 173,5 cm	7,70 kg
Total booth Weight		118,80 kg

- **Standard outside color:** Dark grey or light grey (ABS plastic finish)
- **Standard inside color:** Light grey or dark blue
- **Assembly:** No tools required
- **Approx. Assembly time:** 10 Minutes (2 persons)

STORAGE & SHIPPING:

Included (1) ATA-300 shipping cases on wheels (52,5 Kg)
CASE OUTSIDE - DIM. : 207,1 x 45,72 x 109,22 cm

AIR VENTILATION:

Included (2) H.D. 55 CFM silent whisper 110 or 220 volts fan assembly units CSA approved with (2) electric outlets for accessories.

OPTIONS:

Easy to install working table, double Plexiglas® window, air conditioning
Sound proof flooring, interior division partition systems.

CONSTRUCTION:

Each panel is built with ABS plastic exterior with special isolated soundproof fibreglass panel. Material is fire retardant UL-723.
Inside covering is made with decorative textile 100 % polyester.
Cotton of 9 mm. Woven density and weight of 60 gr. Per meter.
Framing is PVC extrusion with unique connecting concept with industrial Velcro for easy assembly without tools.



